

CAVO DI CONNESSIONE DEGLI ELEMENTI DI BATTERIA



Nostro codice	Sezione (mm ²)	Lunghezza (mm)	Unità per confezione
AS25.75V	25	75	300
AS25.85V	25	85	300
AS25.95V	25	95	300
AS25.110V	25	110	300
AS35.75V	35	75	300
AS35.85V	35	85	300
AS35.95V	35	95	300
AS35.110V	35	110	300
AS35.130V	35	130	250
AS35.150V	35	150	250
AS35.170V	35	170	250
AS50.95V	50	95	250
AS50.110V	50	110	250
AS50.130V	50	130	200
AS50.150V	50	150	200
AS50.170V	50	170	150
AS50.190V	50	190	120
AS50.210V	50	210	120
AS50.300V	50	300	100
AS70.95V	70	95	200
AS70.110V	70	110	200
AS70.130V	70	130	150
AS70.150V	70	150	150
AS70.170V	70	170	120
AS70.190V	70	190	120
AS70.250V	70	250	100
AS70.300V	70	300	80
AS95.95V	95	95	120
AS95.110V	95	110	100
AS95.130V	95	130	76

AS95.170V	95	170	60
AS95.210V	95	210	50
AS120.110V	120	110	30
AS120.170V	120	170	30
AS120.230V	120	230	20
AS120.250V	120	250	20
AS120.300V	120	300	10

-Standard connection = M10

-Connection: welded technique